

Channel profile M(2,5:1)



Outlet section M(2:1)



Dodat s/Delivery with:
2x Slot cover 73x998–20 Z361684
1x Silt basket for D157 art.nr. 408202
1x Slot cover 218x218–30 art.nr. 445784
2x OSB cover 71x996–20 NM16788
1x OSB cover 216x216–30 NM16793

⏚ NM8597 + 2xNM8598 + 91376

Svařovat dle T00267 / Welded according to T00267

Vzdálenost nivelačních šroubů cca 800 mm
Vzdálenost kotev cca 400mm
Pohledové plochy brousit (velikost brusných zrn 240) a polepit páskou

Distance of leveling feet cca 800 mm
Distance of fixing tangs cca 400mm
Visible surfaces to be grinded and covered with protective foil

Material: 1.4301	Tolerance: ISO 2768 – 1m – 2L	Tolerance for welding: EN ISO 13920 – A	Mass: 19.000 kg
ACO Industries k.s. Havlíčkova 260 582 22 Přibyslav, CZ Tel.: +420 569 491 111 www.aco.com www.aco-industries.cz	Drawing NO.: DÜNNBETTFLANSCH – MONOLITHISCHE KONSTRUKTION	Index:	Article: 408055K – MADE TO ORDER	Surface finish: –
	Created by: dsteffl	Reviewed by:		Projection ISO–E; Scale: 1:5

Title: ACO Boxchannel W105/75 L2380 H100/80 E20 D142 F86.5

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Observe copyright by ISO 16016

Created date	Relase date	
14.02.2020		A2