




Dodat s/Delivery with:  
2x Slot cover 73x998-20 Z361684  
1x Silt basket for D157 art.nr. 408202  
1x Slot cover 218x218-30 art.nr. 445784  
2x OSB cover 71x996-20 NM16788  
1x OSB cover 216x216-30 NM16793

± NM8597 + 2xNM8598 + 91376

Svařovat dle T00267 / Welded according to T00267

Vzdálenost nivelačních šroubů cca 800 mm  
Vzdálenost kotev cca 400mm  
Pohledové plochy brousit (velikost brusných zrn 240) a polepit páskou

Distance of leveling feet cca 800 mm  
Distance of fixing tangs cca 400mm  
Visible surfaces to be grinded and covered with protective foil

Material	1.4301	Tolerance	ISO 2768 - 1m - 2L	Tolerance for welding	EN ISO 13920 - A	Mass	19.000 kg
 <b>ACO Industries k.s.</b> Havlíčkova 260 582 22 Pílsyav, CZ Tel.: +420 569 481 111 www.aco.com www.aco-industries.cz	Drawing NO.	DÜNNBETTFLANSCH - MONOLITHISCHE KASTENRINNE		Index	Article	Surface finish	Material
	Created by	dsteffl		Reviewed by		Projection ISO-E	Scale
							1:5
Title							
ACO Boxchannel W105/75 L2380 H100/80 E20 D142 F86.5							
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. Observe copyright by ISO 15016				Created date	14.02.2020	Release date	A2